* We are Custom Chrome *





Replacements for the rear brackets on 4-speed FX models thru 81, or can be used to replace the 82-10 one-piece welded and stamped rear footrest brackets, and the large aluminum rear brackets fitted to 4-speed FL models from 77-84.

- 26366 Left and right brackets alone (1/4" steel plate)
- **26367** Bracket set (includes supports and mounting hardware)



Vibra-Kushion Footpeg Stirrups

Get more comfort without adding floorboards. These stirrups use our Vibra-Kushion footpegs, and are adjustable so that you get the right amount of heel support. Include male clevis' that fit large or small-diameter Vibra-Kushion footpegs.

18973 Chrome, Pair **651800** Black, Pair





Clamp-On Footpeg Sets

1 1/4" clamp-on footpeg kits with three different styles of footpegs come complete with three-piece chrome frame clamps. They will fit all Sportster frames from 82-Up and all 5-speed rubbermount frames.

18887 With O-ring pegs18888 With rubber cush

18888 With rubber cushion pegs18889 With rubber pegs



Küryakyn Footpegs with Clevis & Magnum Quick Clamps

This is our most popular style of highway peg. Using our patented Magnum Quick Clamp, they are a snap to install & provide long-haul comfort. There are several styles of footpegs to choose from with various sized clamps to accommodate most common engine guard diameters. They can be installed on any round tubing (frames or engine guards), but it is important to keep in mind that the footpeg itself will end up perpendicular to the bar to which it is mounted.

605149	ISO-Wings with Clevis & 1 1/4" Quick Clamp (pr)
605150	Dually ISO-Pegs with Clevis & 1 1/4" Magnum Quick Clamp (pr)
605151	Small ISO-Pegs with Clevis & 1 1/4" Magnum Quick Clamp (pr)
605152	Large ISO-Pegs with Clevis & 1 1/4" Magnum Quick Clamp (pr)
605154	Large ISO-Pegs with ISO-Stirrups & 1 1/4" Magnum Quick Clamp (pr)



Küryakyn Offset Highway Pegs

These highway pegs utilize our unique offset mount to allow riders a range of adjustment not possible with other clamp-on style highway pegs. The offset can be rotated 360° in a 4" diameter circle to accommodate tall, short, or average height riders. These can be installed on any round tubing (frames or engine guards), but it is important to keep in mind that the footpeg itself will end up perpendicular to the bar to which it is mounted.

605146Dually ISO-Pegs with Offset & 1 1/4" Magnum Quick Clamps (pr)605147Small ISO-Pegs with Offset & 1 1/4" Magnum Quick Clamps (pr)605148Large ISO-Pegs with Offset & 1 1/4" Magnum Quick Clamps (pr)